

ninebot®



Specifications

Model	Ninetbot PTR E
Primary Materials	Magnesium alloy+ aluminum alloy+ LEXAN resin
Weight	52 lbs
Machine Size	15.4" x 23.2" x 43.3"~55.1"
Shipping Carton Sizes	Mainframe: 24.4" x 17.3" x 18.5" (50 lbs) Operation Bar: 44.9" x 5.5" x 3.7" (5 lbs)
Recommended Max Payload	250 lbs
Max. Speed	12.5 Mph
Max Range	12.5 Miles (full battery charge, flat terrain, dependant on riders weight)
Max. Slope	20 degrees (incline / decline)
Speed Settings	Speed Mode: Can be adjusted using the Ninebot App
Battery	Lithium 55V/450Wh
Motor	2 x 1350W
Tire/Rim Size	85/50-12 custom tires, 12" x 2.7" rims
Back-up System	Redundant electronic control system
Remote Control Keys	Multi-Function Wireless Key FOB (2 pieces)
Charger / Charge Time	1 x standard charger, 120W, 3-4 hours for full charge
Wireless	Bluetooth wireless connection. Remote control using 'Ninebot' Smartphone APP
NineDroid APP Display Panel	Displays battery capacity; mileage; speed; temperature; firmware versions; speed-limited mode; remote control mode; locked mode; Bluetooth connection; Warnings; and System Alerts
Handlebar Dashboard	Readable in sunlight; automatic luminance adjustment; power, mileage, speed, riding time, internal temperature, firmware, switch off limit speed mode, remote control mode, lock mode, Bluetooth connection display; alarm, fault status & code display

Remarks: Specifications above for reference only. Subject to change without prior notice.



Online: www.NinebotUS.com
Tel. (862) 930-4079
Email: sales@ninebotus.com